

WCF

WINDOWS R410A



Airwell



WCF

Windows R410A

50Hz R410A Window units to meet marketing requirement.

COMMON FUNCTIONS

- Cooling only
- Sleep mode
- ON/OFF Timer
- Clock and temperature display
- Auto Swing
- Four directions Air Flow
- Auto restart memory (from power failure)



WCF009-012



IR remote control

		WCF009 AWWR-WCF009-C11	WCF012 AWWR-WCF012-C11	
Technical specifications	Function	Cooling	Cooling	
	Rated Voltage	220V	220V	
	Rated Frequency	50Hz	50Hz	
	Total Capacity	W/Btu/h	2500/8550	3500/12000
	Power Input	W	910	1270
	Rated Input	W	1150	1550
	Rated Current	A	5,8	7,8
	Air Flow Volume (H/M/L)	m ³ /h	360/310/260	480/430/380
	Dehumidifying Volume	l/h	0,8	1,6
	EER / C.O.P	W	2,75	2,76
Indoor side	Fan Type-Piece	Cross flow fan - 1	Cross flow fan - 1	
	Sound Pressure Level (H/M/L)	dB(A)	49/47/45/	53/51/49
	Sound Power Level (H/M/L)	dB(A)	59/57/55	63/61/59
Outdoor side	Compressor Type	Rotary	Rotary	
	Working Temp Range	°C	18-43	18-43
	Isolation	l	l	l
	Moisture Protection	IP24	IP24	IP24
	Dimension (W/H/D)	mm	450x350x580	560x375x618
	Dimension of Package (W/H/D)	mm	518x395x668	661x463x727
	Net Weight /Gross Weight	kg	36/39	48/52
	Refrigerant Charge	kg	R410A: 0.48	R410A: 0.92
	Loading quantity	20' Container	216	135
		40' Container	444	285
40' High Cube Container		518	342	



Airwell
Your official dealer

Airwell Group
1bis, Avenue du 8 mai 1945
Saint Quentin en Yvelines
78284 GUYANCOURT
France
Tel. +33 (0)1 39 44 78 00
Fax +33 (0)1 39 44 65 17
www.airwell.com
contact@airwell-group.com